

Z o.

Description

Quantity (Nos)

3 Ball

2 Adapter

1 Body

5 Stem

6 Stem Seal

7 Gland

8 Gland Seal

4 Ball Seat Ring

9 Gland Nut 10 Handle 11 Handle Sleeve 12 Handle Nut

DIMENSIONAL DETAILS	

Part No	Size	A	L	Н	PORT	PRESSURE TEST
BAX - 4BVFF	1/4"	58.00	91.00	42.00	7.00	3000 Psi
BAX - 6BVFF	3/8"	58.00	89.00	42.00	8.50	3000 Psi
BAX - 8BVFF	1/2"	68.00	110.00	47.00	10.50	3000 Psi
BAX - 12BVFF	3/4"	77.00	77.00 110.00	52.00	16.00	1500 Psi
BAX - 16BVFF	1"	85.00	85.00 125.00 58.00	58.00	19.00	1500 Psi

VALVES CAN BE SUPPLIED TO MEET CURRENT REVISION NACE MR-01-75	VALVES CAN BE
TEST AVAILABLE UPON REQUESTS : VIBRATION, TEMPERATURE, CYCLING HELIUM etc.	TEST AVAILABL
1000 PSI	NITROGEN TEST
150 PSI	PNEUMATIC TEST 150 PSI
(UPTO 1/2" - 3000 PSI & 3/4" / 1" - 1500PSI)	
1.5 TIMES THE WORKING PRESSURE RATING	HYDRO TEST
c) BSPT THREAD AS PER BS 21	
b) BSPP THREAD AS PER BS 2779	
a) NPT THREAD AS PER ANSI B 2.1	THREADS
b)THREAD SOLVENT - LOCTITE 542	
a)ANTI SEIZE — NEVER—SEEZ	LUBRICANT
PRESSURE RATING.	
LOGO/BRAND NAME, MODEL NO., M.O.C,	MARKING
MATT FINISH	VISUAL FINISH
MS/SS POWDER COATED HANDLE WITH PVC SLEEVE.	HANDLE
FOR 1/4" TURN SHUT OFF.	STOPPER
JRE UP TO	
a) PTFE AS STD UP TO MAX. 250°C & GRAFOIL AS	PACKING
NON RISING STEM.	
2 PIECE REDUCED PORT/FLOATING BALL WITH SLOTTED	DESIGN
BODY & ALL OTHER SPARES - ASTM A 479 GR.316/316L.	M.O.C.
DESCRIPTION	TITLE
TECHNICAL SPECIFICATION	

*NOTE : ALL DIMENSIONS IN MM ARE FOR REFERENCE ONLY AND ARE SUBJECT TO CHANGE WITHOUT PRIOR INTIMATION.

BAXCELL

BAXCELL Instrument Valves & Fittings Pvt. Ltd. (An ISO 9001: 2000 COMPANY)

Title: TWO PIECE REDUCED PORT, SCREWED
FND RALL VALVE

DRAWN BY

DRAWN G/MODEL NO.:

BAX - BV2P - 01

BAX - BV2P - 01

OO

OO

OO

APPROVED BY: